

BLUE LAVATM

HOT PVC CEMENT

Oatey® Hot Medium Blue Lava™ PVC Cement is formulated for wet conditions or situations involving fast installation of pressurization of PVC pipe and fittings up to 6" diameter with interference fit.

DESCRIPTION

- Extremely fast setting thick formula clings to pipe in wet and underwater applications
- Preferred formula for emergency, repair, and cut in work
- Medium body blue cement for use on all schedules and classes of PVC pipe and fittings up to 6" diameter with interference fit
- No primer needed where local code permits
- Recommended for potable water, sewer, and DWV applications
- Recommended application temperature 40°F to 110°F / 4°C to 43°C
- Meets ASTM D2564



| Product Number | Size | Description | Carton Qty |
|---|--------|--|------------|
| 32160 | 4 oz. | Hot Medium Blue Lava PVC Cement | 24 |
| 32161 | 8 oz. | Hot Medium Blue Lava PVC Cement | 24 |
| 32162 | 16 oz. | Hot Medium Blue Lava PVC Cement | 24 |
| 32163 | 32 oz. | Hot Medium Blue Lava PVC Cement | 12 |
| 32164 | Gallon | Hot Medium Blue Lava PVC Cement | 6 |
| California Compliant: SCAQMD Rule 1168-23 | | | |
| 32160V | 4 oz. | Hot Medium Blue Lava PVC Cement - Rule 1168-23 | 24 |
| 32161V | 8 oz. | Hot Medium Blue Lava PVC Cement - Rule 1168-23 | 24 |
| 32162V | 16 oz. | Hot Medium Blue Lava PVC Cement - Rule 1168-23 | 24 |
| 32163V | 32 oz. | Hot Medium Blue Lava PVC Cement - Rule 1168-23 | 12 |
| 32164V | Gallon | Hot Medium Blue Lava PVC Cement - Rule 1168-23 | 6 |













Call your Oatey Sales Representative for more information.











©2022 CaterySCS. All Rights Reserved. This information is based on data believed to be reliable but Oatey makes no warranties, express or implied, as to its accuracy and assumes no liability arising out of its use. The data listed falls within the normal range of product properties but should not be