



UN-PURPLE PRIMER

Purple Primer Without Purple Stains

Key Features & Benefits:

- Appears clear but shows purple under UV light
- Removes surface dirt, grease and grime while pre-softening pipe
- Allows for a fast, secure solvent weld
- Easy to apply on any diameter of PVC or CPVC piping with included in-lid dauber; not recommended for use on ABS piping installations
- Recommended application temperature of 40°F to 110°F / 4°C to 43°C
- All Hercules solvent cement and primer products are certified to UL Greenguard Gold



Pipe under UV light

Part Number	Description
60445	16 oz. PVC and CPVC Un-Purple Primer
60447	32 oz. PVC and CPVC Un-Purple Primer

Low VOC, high performance primer that meets California South Coast Air Quality Management Districts (SCAQMD) 1168/316A or BAAQMD Method 40 requirements, meets ASTM Standard F656 and complies with NSF/ANSI 61 health effects requirements

Call your Oatey Sales Representative for more information.

Find us on

©2024 Oatey/SCS. All Rights Reserved. This information is based on data believed to be reliable but Oatey makes no warranties, express or implied, as to its accuracy and assumes no liability arising out of its use. The data listed falls within the normal range of product properties but should not be used to establish specification limits or used alone as the basis of design. Oatey's liability to purchasers is expressly limited to the terms and conditions of sale. Oatey is a trademark of Oatey Co. Oatey Co. is part of the Oatey family of companies. All other trademarks can be found on www.Oatey.com.