

1. Identification

Product identifier	P12 or P12G PVC Cement
Other means of identification	
SDS number	3102E
Recommended use	Joining PVC Pipes
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Company Name	William H. Harvey Company
Address	4334 South 67th Street Omaha, NE 68117
Telephone	402-331-1175
E-mail	info@oatey.com
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)
Emergency First Aid	1-877-740-5015
Contact person	MSDS Coordinator

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Acute toxicity, oral	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist/vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/eye protection/face protection.
Response	If swallowed: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May form explosive peroxides. Contains a chemical classified by the US EPA as a suspected possible carcinogen.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Tetrahydrofuran	109-99-9	30 - 60
Acetone	67-64-1	10 - 30
Cyclohexanone	108-94-1	10 - 30
Polyvinyl chloride	9002-86-2	10 - 30
Methyl ethyl ketone	78-93-3	5 - 10
Silica, amorphous, fumed	112945-52-5	1 - 5

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor. This product contains tetrahydrofuran that may form explosive organic peroxide when exposed to air or light or with age.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not taste or swallow. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Components	Type	Value
Polyvinyl chloride (CAS 9002-86-2)	STEL	5 ppm
	TWA	1 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m ³
		1000 ppm
Cyclohexanone (CAS 108-94-1)	PEL	200 mg/m ³
		50 ppm
Methyl ethyl ketone (CAS 78-93-3)	PEL	590 mg/m ³
		200 ppm
Tetrahydrofuran (CAS 109-99-9)	PEL	590 mg/m ³
		200 ppm

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Polyvinyl chloride (CAS 9002-86-2)	TWA	5 mg/m ³	Respirable fraction.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Silica, amorphous, fumed (CAS 112945-52-5)	TWA	15 mg/m ³	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
		0.8 mg/m ³	
		20 mppcf	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Cyclohexanone (CAS 108-94-1)	STEL	50 ppm	
	TWA	20 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL	300 ppm	
	TWA	200 ppm	
Polyvinyl chloride (CAS 9002-86-2)	TWA	3 mg/m ³	Respirable particles.
	TWA	3 mg/m ³	
Tetrahydrofuran (CAS 109-99-9)	STEL	100 ppm	
	TWA	50 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m ³
		250 ppm
Cyclohexanone (CAS 108-94-1)	TWA	100 mg/m ³
		25 ppm
Methyl ethyl ketone (CAS 78-93-3)	STEL	885 mg/m ³
		300 ppm
	TWA	590 mg/m ³
		200 ppm
Silica, amorphous, fumed (CAS 112945-52-5)	TWA	6 mg/m ³
	STEL	735 mg/m ³
250 ppm		
TWA		590 mg/m ³
	TWA	200 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
Cyclohexanone (CAS 108-94-1)	80 mg/l	1,2-Cyclohexanediol, with hydrolysis	Urine	*

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
	8 mg/l	Cyclohexanol, with hydrolysis	Urine	*
Methyl ethyl ketone (CAS 78-93-3)	2 mg/l	MEK	Urine	*
Tetrahydrofuran (CAS 109-99-9)	2 mg/l	Tetrahydrofuran	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Cyclohexanone (CAS 108-94-1) Skin designation applies.

US - Tennessee OELs: Skin designation

Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin.

Tetrahydrofuran (CAS 109-99-9) Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Physical state Liquid.

Form Transparent to opaque liquid.

Color Clear or gray.

Odor Solvent.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling range 151 °F (66.1 °C)

Flash point 14.0 - 23.0 °F (-10.0 - -5.0 °C)

Evaporation rate 5.5 - 8

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 145 mm Hg @ 20 C

Vapor density 2.5

Relative density 0.9 +/- 0.02

Solubility(ies)

Solubility (water) Negligible

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity 1200 - 2500 cP

Other information

Bulk density 7.5 lb/gal

VOC < 510 g/l SCAQMD 1168/M316A

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Amines. Ammonia. Caustics. Chlorine. Fluorine. Isocyanates.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact Causes serious eye irritation.

Ingestion Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Harmful if swallowed. May be fatal if swallowed and enters airways.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 15700 mg/kg, 24 Hours

Components	Species	Test Results
Inhalation		
<i>Vapor</i>		
LC50	Rat	76 mg/l, 4 Hours
Oral		
LD50	Rat	5800 mg/kg
Cyclohexanone (CAS 108-94-1)		
<u>Acute</u>		
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 6.2 mg/l, 4 Hours
Oral		
LD50	Rat	2650 mg/kg 1890 mg/kg 1620 mg/kg
Methyl ethyl ketone (CAS 78-93-3)		
<u>Acute</u>		
Dermal		
LD50	Rat	6400 mg/kg
Inhalation		
<i>Vapor</i>		
LC50	Rat	34.5 mg/l, 4 Hours
Oral		
LD50	Rat	2600 mg/kg
Tetrahydrofuran (CAS 109-99-9)		
<u>Acute</u>		
Inhalation		
LC50	Rat	53.9 mg/l, 4 Hours
Oral		
LD50	Rat	1650 mg/kg
Skin corrosion/irritation	Causes skin irritation. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure. In 2012 USEPA Integrated Risk Information System (IRIS) reviewed a two species inhalation lifetime study on THF conducted by NTP (1998). Male rats developed renal tumors and female mice developed liver tumors while neither the female rats nor the male mice showed similar results. Because the carcinogenic mechanisms could not be identified clearly in either species for either tumor, the EPA determined that the male rat and female mouse findings are relevant to the assessment of carcinogenic potential in humans. Therefore, the IRIS review concludes that these data in aggregate indicate that there is "suggestive evidence of carcinogenic potential" following exposure to THF by all routes of exposure. This product contains polyvinyl chloride (PVC) that is not a fabricated product, and is therefore, defined and regulated as a toxic and hazardous substance under 29 C.F.R. § 1910.1017 due to the presumed presence of residual vinyl chloride monomer. The concentrations of residual vinyl chloride calculated to be contained in this product are well below the threshold for classification in accordance with 29 C.F.R. § 1910.1200.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Cyclohexanone (CAS 108-94-1)	3 Not classifiable as to carcinogenicity to humans.	
Polyvinyl chloride (CAS 9002-86-2)	3 Not classifiable as to carcinogenicity to humans.	

Silica, amorphous, fumed (CAS 112945-52-5)
Tetrahydrofuran (CAS 109-99-9)

3 Not classifiable as to carcinogenicity to humans.
2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Polyvinyl chloride (CAS 9002-86-2)

Cancer

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure

May cause respiratory irritation. May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure

Not classified.

Aspiration hazard

May be fatal if swallowed and enters airways.

Chronic effects

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Acetone (CAS 67-64-1)			
Aquatic			
<i>Acute</i>			
Crustacea	LC50	Daphnia pulex	8800 mg/l, 48 Hours
Fish	LC50	Pimephales promelas	7163 mg/l, 96 Hours
<i>Chronic</i>			
Crustacea	NOEC	Daphnia magna	> 79 mg/l, 21 days
Cyclohexanone (CAS 108-94-1)			
Aquatic			
<i>Acute</i>			
Fish	LC50	Pimephales promelas	527 mg/l, 96 Hours
Methyl ethyl ketone (CAS 78-93-3)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia magna	5091 mg/l, 48 Hours
Fish	LC50	Pimephales promelas	3220 mg/l, 96 Hours
Tetrahydrofuran (CAS 109-99-9)			
Aquatic			
<i>Acute</i>			
Crustacea	LC50	Daphnia magna	5930 mg/l, 24 Hours
Fish	LC50	Pimephales promelas	2160 mg/l, 96 Hours
<i>Chronic</i>			
Algae	NOEC	Scenedesmus quadricauda	3700 mg/l, 8 days

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Acetone (CAS 67-64-1)	-0.24
Cyclohexanone (CAS 108-94-1)	0.81
Methyl ethyl ketone (CAS 78-93-3)	0.29
Tetrahydrofuran (CAS 109-99-9)	0.46

Mobility in soil

No data available.

Other adverse effects

The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	149, B52, IB2, T4, TP1, TP8
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242

IATA

UN number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number	UN1133
UN proper shipping name	ADHESIVES
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)

Listed.

Cyclohexanone (CAS 108-94-1)	Listed.
Methyl ethyl ketone (CAS 78-93-3)	Listed.
Tetrahydrofuran (CAS 109-99-9)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Polyvinyl chloride (CAS 9002-86-2)	Cancer Central nervous system Liver Blood Flammability
------------------------------------	--

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories	Flammable (gases, aerosols, liquids, or solids) Acute toxicity (any route of exposure) Skin corrosion or irritation Serious eye damage or eye irritation Specific target organ toxicity (single or repeated exposure) Aspiration hazard
-------------------------------------	--

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1)	6532
Methyl ethyl ketone (CAS 78-93-3)	6714

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1)	35 %WV
Methyl ethyl ketone (CAS 78-93-3)	35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1)	6532
Methyl ethyl ketone (CAS 78-93-3)	6714

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Acetone (CAS 67-64-1)	Low priority
Cyclohexanone (CAS 108-94-1)	Low priority
Methyl ethyl ketone (CAS 78-93-3)	Low priority

US state regulations

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)
Cyclohexanone (CAS 108-94-1)
Methyl ethyl ketone (CAS 78-93-3)
Silica, amorphous, fumed (CAS 112945-52-5)
Tetrahydrofuran (CAS 109-99-9)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)
Cyclohexanone (CAS 108-94-1)
Methyl ethyl ketone (CAS 78-93-3)
Polyvinyl chloride (CAS 9002-86-2)
Tetrahydrofuran (CAS 109-99-9)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)
Cyclohexanone (CAS 108-94-1)
Methyl ethyl ketone (CAS 78-93-3)
Silica, amorphous, fumed (CAS 112945-52-5)
Tetrahydrofuran (CAS 109-99-9)

US. Rhode Island RTK

Acetone (CAS 67-64-1)
Cyclohexanone (CAS 108-94-1)
Methyl ethyl ketone (CAS 78-93-3)
Polyvinyl chloride (CAS 9002-86-2)
Tetrahydrofuran (CAS 109-99-9)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	03-February-2019
Revision date	-
Version #	01
HMIS® ratings	Health: 3 Flammability: 3 Physical hazard: 0

NFPA ratings



Disclaimer

William H. Harvey Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.