



# POOL-TITE™

## HOT BLUE PVC CEMENT

**MORE COMPLETED POOL JOBS  
MEANS MORE REVENUE FOR YOU!**

Pool-Tite Hot Blue cement is designed to maximize your productivity for pool installations or repairs for both wet and dry solutions.

### FAST

- Pool-Tite cement sets up fast
- Sets up in just 1–2 minutes (see chart)

30°F to 50°F	50°F to 70°F	70°F to 100°F
4–5 Minutes	3–4 Minutes	1–2 Minutes

- Bond strengths in excess of 250 psi in 10 minutes under lab conditions

**System may be hydrostatically tested up to 75 PSI after 15 minutes and up to 180 PSI after 30 minutes.\***

\* At temperatures above 60°F and up to 2" pipe diameter.

### EASY

2346S Shown

- Versatile cement used in many applications
- Recommended for use on all schedules and classes of flexible and rigid PVC pipe and fittings up to 6" with interference fit
- No primer needed on non-pressure DWV up to 4" where local codes permit

Product Number	Size	Description	Carton Qty
2366S	4 oz.	Pool-Tite PVC Medium "Hot" Blue Cement	24
2356S	8 oz.	Pool-Tite PVC Medium "Hot" Blue Cement	24
2346S	16 oz.	Pool-Tite PVC Medium "Hot" Blue Cement	24
2336S	32 oz.	Pool-Tite PVC Medium "Hot" Blue Cement	12
2324	Gallon	Pool-Tite PVC Medium "Hot" Blue Cement	6

### California Compliant: SCAQMD Rule 1168-23

2366SV	4 oz.	Pool-Tite PVC Medium "Hot" Blue Cement - Rule 1168-23	24
2356SV	8 oz.	Pool-Tite PVC Medium "Hot" Blue Cement - Rule 1168-23	24
2346SV	16 oz.	Pool-Tite PVC Medium "Hot" Blue Cement - Rule 1168-23	24
2336SV	32 oz.	Pool-Tite PVC Medium "Hot" Blue Cement - Rule 1168-23	12
2324V	Gallon	Pool-Tite PVC Medium "Hot" Blue Cement - Rule 1168-23	6

