



UNI-WELD® 7300 SERIES CLEAR CLEANER TECHNICAL SPECIFICATION

Job Name _____	Item # _____
Location _____	
Engineer _____	Contractor _____
PO # _____	Tag _____
Representative _____	

SPECIFICATIONS

- Uni-Weld 7300 Series Clear Cleaner is recommended for use with ABS, PVC and CPVC pipe and fittings.
- This product is compliant with California South Coast Air Quality Management District (SCAQMD) Rule 1171/M24 and various environmental requirements.
- **This product is not for use in a system using or being tested by compressed air or gases.**

APPLICATION / USES

- Clear Cleaner is formulated to remove dirt and oil from the surface of the piping in preparation for solvent welding.

PROPERTIES / INGREDIENTS

INGREDIENTS (CAS Number):

Acetone (67-64-1), Cyclohexanone (108-94-1), Methyl Ethyl Ketone (78-93-3), Tetrahydrofuran (109-99-9)

VOC

Maximum VOC per SCAQMD 1171/ EPA method 24: < 25 g/L

CHEMICAL PROPERTIES

Appearance	Clear Liquid
Density	6.71 ± 0.2 lbs/gallon
Shelf Life	3 Years from Mfg. Date



PRODUCT NUMBER	SIZE	DESCRIPTION	CTN. QTY
7366S	4 oz.	Clear Cleaner	24
7356S	8 oz.	Clear Cleaner	24
7346S	16 oz.	Clear Cleaner	24
7336S	32 oz.	Clear Cleaner	12
7324	Gallon	Clear Cleaner	6



UNI-WELD® 7300 SERIES CLEAR CLEANER TECHNICAL SPECIFICATION

DIRECTIONS FOR USE

Read all directions carefully before using this product.

- Do not breathe vapors. Use only in well ventilated area. If forced air ventilation is used, be sure it does not cause a fire hazard from solvent vapors. If adequate ventilation cannot be provided, wear a NIOSH-approved respirator for organic solvents.
 - Do not use or store near heat, sparks, or flames. Do not smoke, eat or drink when using. Do not take internally. Vapors may accumulate in low places and may ignite explosively.
 - Store at temperatures between 40F and 110F; Use at temperatures between -15F and 110F.
 - Keep container closed when not in use.
 - Avoid eye and skin contact - wear safety glasses with side shields and wear rubber gloves.
 - Do not thin.
1. Square pipe ends and remove all burrs and dirt.
 2. Check dry fit of pipe and fitting. Pipe should easily go 1/3 of the way into the fitting. If the pipe bottoms, it should be snug.
 3. Use a suitable applicator at least 1/2 the size of the pipe diameter. For larger size pipe systems use a natural bristle brush or roller.
 4. Apply thoroughly to outside surface of the pipe to the depth of the fitting and inside of the fitting socket.
 5. Use appropriate solvent cement for the pipe being joined. Use sparingly on ABS pipe and fittings. **DO NOT TEST WITH AIR.**

This product is not for use with caustic or acidic chemical solutions. Consult Technical Department for more information.

PRECAUTIONS

Read all information carefully before using this product.

DANGER: EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRES. MAY IRRITATE EYES AND SKIN. VAPOR HARMFUL. MAY IRRITATE RESPIRATORY TRACT AND CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. HARMFUL OR FATAL IF SWALLOWED.

May cause irritation to eyes, skin, and nose, throat, and respiratory tract. May cause coughing, sore throat, difficulty breathing, headache, dizziness, nausea. Long term repeated overexposures to solvents may cause damage to the brain, nervous system, reproductive system, respiratory system, mucous membranes, liver, and kidneys. **KEEP OUT OF REACH OF CHILDREN.**

FIRST AID: If swallowed, **DO NOT INDUCE VOMITING.** Drink water and call a doctor or poison control center immediately. This product may be aspirated into the lungs and cause chemical pneumonitis, a potentially fatal condition. If contact with eyes, flush with water for 15 minutes and seek medical attention if irritation persists. If contact with skin, wash with soap and water. If inhaled and ill feelings develop, get fresh air and obtain medical attention if ill feelings persist. **FOR EMERGENCY FIRST AID INSTRUCTIONS CALL 1-877-740-5015.**

FIRE: Use dry chemical, foam, or carbon dioxide extinguisher. Water spray may be applied to reduce potential vapors or for cooling. Burning liquid extinguished with water will float and may re-ignite on surface of water.

SPILLS: Remove all sources of ignition and ventilate area. Personnel cleaning up the spill should wear appropriate personal protective equipment, including respirators if vapor concentrations are high. Soak up spill with absorbent material. Put absorbent material in covered, labeled metal containers. Dispose of in accordance with local regulations.

A fire or explosion may result if dry granular calcium hypochlorite is used to disinfect plastic piping systems and is exposed to organic vapors found in solvent cements, cleaners or primers. Do not disinfect piping system with dry granules. Do not store dry granular calcium hypochlorite near solvent cements, cleaners or primers. **DO NOT REUSE EMPTY CONTAINER. KEEP OUT OF REACH OF CHILDREN.**

Refer to material safety data sheet for more information.

Before purchase and use of a product, review the product application and be certain the product, installation and use will be in compliance with any applicable codes and regulations.