

GREAT WHITE PIPE JOINT COMPOUND WITH PTFE

For Use On Plastic Or Metal Threads

White, non-hardening, non-separating, nontoxic paste. Lubricates and seals all threaded joints - can be used on plastic or metal threads. For use with water, steam, caustics, or dilute acid lines of PVC, CPVC, ABS, cycolac, polypropylene, iron, steel, or copper.

Withstands up to 3,000 psi on gases from -50 to $+400^{\circ}F$ (-46 to 204°C), and 10,000 psi on liquids from -50 to $+500^{\circ}F$ (-46 to 260°C).





	Catalogue Number	Description	Quantity Per Case		Approximate Case Shipping Weight	
	48007	Great White Pipe Joint Compound w/PTFE - 29 mL tube	12	1.2 lb	0.5 kg	
	48008	Great White Pipe Joint Compound w/PTFE - 118 mL	12	7.3 lbs	3.3 kg	
	48009	Great White Pipe Joint Compound w/PTFE - 237 mL	12	11.5 lbs	5.2 kg	





©2020 DaterySCS. All Rights Reserved. This information is based on data believed to be reliable but. Catey makes no warranties, express or implied, as to its accuracy and assumes no liability arising out of its use. The data listed falls within the normal range of product properties but should not be used to establish specification limits or used alone as the basis of design. Datery's lability to purchasers is expressly limited to the terms and conditions of sale. Catey is a trademark of Datery Co. Statey Co. is part of the Datey family of companies. All other trademarks can be found on www.oatev.ca