



WHITE TAPE

THREAD SEALING TAPE

MASTERS® WHITE TAPE seals all metal and plastic threaded connections against leakage at temperatures from -400°F to +600°F (-240°C to +316°C).

MASTERS® WHITE TAPE is non-corrosive, non-flammable, clean, easy to use and is available in a wide range of widths and lengths. Joints disassemble easily, even after years of service.

Because it is chemically inert, MASTERS® WHITE TAPE is impervious to virtually everything including:

- Acids & Alkalis
- Air
- Ammonia
- Chlorine
- CO₂
- Fuels
- Gasoline
- Hydrocarbons
- Kerosene
- Nitrogen
- Oxygen
- Refrigerants (most)
- Solvents
- Steam
- Water

Directions:

- Make sure threads are clean and remove any shreds of previously applied tape.
- Beginning with the first thread of the male end, wrap tape in the direction of the thread spiral. Use enough for a good seal.
- Tighten the joint using a wrench.



Catalogue Number	Description	Quantity Per Case	Approximate Case Shipping Weight		UPC	i2of5
TWB480P	1/2" x 480" (1.27 cm x 12.19 m) Roll Economy/Low Density	200	6 lbs	2.7 kg	067001000934	20067001000938
TWB480P10	1/2" x 480" (1.27 cm x 12.19 m) Economy Tape 10 pack polybag sleeve	20 packs	4.8 lbs	2.2 kg	067001006103	40067001006101



Find us on



©2019 OateySCS. All Rights Reserved. This information is based on data believed to be reliable but Oatey makes no warranties, express or implied, as to its accuracy and assumes no liability arising out of its use. The data listed falls within the normal range of product properties but should not be used to establish specification limits or used alone as the basis of design. Oatey's liability to purchasers is expressly limited to the terms and conditions of sale. Oatey is a trademark of Oatey Co. Oatey Co. is part of the Oatey family of companies. All other trademarks can be found on Oatey.com.