



WHITE TAPE

THREAD SEALING TAPE

MASTERS® WHITE TAPE seals all metal and plastic threaded connections against leakage at temperatures from -400°F to +600°F (-240°C to +316°C).

MASTERS® WHITE TAPE is non-corrosive, non-flammable, clean, easy to use and is available in a wide range of widths and lengths. Joints disassemble easily, even after years of service.

Because it is chemically inert, MASTERS® WHITE TAPE is impervious to virtually everything including:

- Acids & Alkalis
- Air
- Ammonia
- Chlorine
- CO₂
- Fuels
- Gasoline
- Hydrocarbons
- Kerosene
- Nitrogen
- Oxygen
- Refrigerants (most)
- Solvents
- Steam
- Water



Directions:

- Make sure threads are clean and remove any shreds of previously applied tape.
- Beginning with the first thread of the male end, wrap tape in the direction of the thread spiral. Use enough for a good seal.
- Tighten the joint using a wrench.

Catalogue Number	Description	Quantity Per Case	Approximate Case Shipping Weight	
TWB480G	1/2" x 480" (1.27 cm x 12.19 m) Roll	200	10 lbs	4.5 kg
TWC480G	3/4" x 480" (1.91 cm x 12.19 m) Roll	12	1 lb	0.5 kg



©2020 OateySCS. All Rights Reserved. This information is based on data believed to be reliable but Oatey makes no warranties, express or implied, as to its accuracy and assumes no liability arising out of its use. The data listed falls within the normal range of product properties but should not be used to establish specification limits or used alone as the basis of design. Oatey's liability to purchasers is expressly limited to the terms and conditions of sale. Oatey is a trademark of Oatey Co. Oatey Co. is part of the Oatey family of companies. All other trademarks can be found on www.oatey.ca.