



PLUMBER'S PUTTY TECHNICAL SPECIFICATION

Job Name _____	Item # _____
Location _____	
Engineer _____	Contractor _____
PO # _____	Tag _____
Representative _____	

DESCRIPTION

Harvey Plumber's Putty is specifically designed for plumbing applications. It provides a waterproof seal between two rigid surfaces. Plumber's Putty is a long lasting, easy to use fixture setting compound for setting frames, faucets and basket strainers. It remains flexible and resilient and will not harden, shrink, crack or crumble.

APPROVALS AND LISTINGS

- Meets Federal Specification TT-P-1536A.

APPLICATION / USES

- Harvey Plumber's Putty can be used for setting frames, faucets and basket strainers.

Consult Oatey Technical Department for applications not specifically referenced above.

PHYSICAL PROPERTIES / INGREDIENTS

NON-HAZARDOUS INGREDIENTS (CAS Number)

Hydrocarbon Oils (64742-52-5), Limestone (1317-65-3), Talc (14807-96-6), Clays (68953-58-2), Blown Canola Oils (129828-25-7)

VOC

< 20 g/L (< 2.0% by weight) after accounting for water and other exempt solvents.

PHYSICAL/CHEMICAL PROPERTIES

Appearance/Odor	Beige Putty / Mild Petroleum Scent
Specific Gravity	2.0
Solubility in Water	Insoluble
Drying Time	No wait required
Shelf Life	1 year from manufacture date



PRODUCT SELECTOR

PLUMBER'S PUTTY			
✓	Product Number	Size	Packing
	43010	14 oz.	24
	43050	3 lbs.	6
	43105	5 lbs.	6

PRECAUTIONS

Read all cautions and directions carefully before using this product. DO NOT USE PLUMBER'S PUTTY ON MARBLE, GRANITE, LIMESTONE OR ANY OTHER DIMENSIONAL STONE. DO NOT USE ON ABS OR OTHER PLASTICS. Consult manufacturer of these materials for recommended sealants. Keep container closed when not in use. DO NOT REUSE EMPTY CONTAINER. KEEP OUT OF REACH OF CHILDREN AND PETS.

Refer to material safety data sheet for more information.

For emergency first aid help, call 1-877-740-5015.

DIRECTIONS

All surfaces must be dry and free from hardened putty, dirt, wax, oil and grease. Remove debris by wiping with cloth, scraper or wire brush as needed and dry surface. Knead putty in hands and form a long cord-like shape. Lay out the cord-like putty on the surface to be sealed, overlapping the ends. Place the fixture over the bead, attach and secure the fixture in place. Excess Plumber's Putty should squeeze out from around the fixture ensuring sufficient putty has been applied and a continuous seal has been made. Remove excess with a putty knife.

Access BIM/Revit content through www.oatey.com