

HIGH TEMPERATURE SILICONE SEALANT

MASTERS® HIGH TEMPERATURE SILICONE SEALANT creates a water tight, mildew and crack resistant seal. The re-sealable, removable cap keeps product from drying out after opening. It is oxygen sensor safe and can be used to replace cork, felt rubber or asbestos gaskets.

MASTERS® HIGH TEMPERATURE SILICONE SEALANT is rated for interior/exterior use from -85°F to +500°F (-65°C to +260°C) consistent or 600°F (316°C) intermittent.

It is ideal for:

- Ovens
- Flues on Gas Appliances
- Metal Stacks
- Ductwork
- Tub/Shower Surrounds
- · Kitchen and Bathroom Sinks
- Siding
- Window Frames
- Tiling
- Countertops





Directions:

- All surfaces must be clean, free of dirt, oil, old silicone and other debris that could deter adhesion.
- Cut nozzle to desired opening size and cut tip off of cartridge.
- Run a continuous bead along surface, keeping the silicone tube ahead of nozzle.
- Tool to a smooth finish. Excess, uncured sealant can be removed with solvent.
- Allow MASTERS® HIGH TEMPERATURE SILICONE SEALANT to cure fully before exposing to water, approximately 24 hours (dries to the touch in approximately 30 minutes).
- Store in a cool dry place between 40°F & 90°F (4°C & 32°C).

Catalogue Number	Description	Quantity Per Case	Approximate Case Shipping Weight	
RED-302	300 mL Cartridge - Red	12	10.2 lbs	4.6 kg
BLACK-302	300 mL Cartridge - Black	12	10.2 lbs	4.6 kg

MASTERS® High Temperature Silicone Sealant is Not Paintable

* RED-302 only



























