



# TRIM PLUS

## INTERIOR/EXTERIOR ACRYLIC PAINTER'S CAULK

MASTERS® TRIM PLUS acrylic caulk is ideal for use in new construction or renovations. The 300mL cartridge is professional grade and the re-sealable cap helps prevent the product from drying out after opening.

MASTERS® TRIM PLUS is rated for interior and exterior use from -18°C to +71°C (0°F to +160°F) once cured. It is paintable in approximately 2 hours, cleans up easily with water, and leaves a professional finish between walls and cabinetry, baseboards, wainscoting, door casing, window casing, crown moulding, and mitred joints.



### DIRECTIONS:

- All surfaces must be clean, free of dirt, oil, old silicone and other debris that could deter adhesion.
- Remove cap and cut nozzle to desired angle and opening size.
- Run a continuous bead along the joint, keeping the cartridge ahead of the nozzle.
- Tool to a smooth finish. Excess, uncured sealant can be removed with soap and water.
- Allow MASTERS® TRIM PLUS to cure fully before exposing to water, approximately 72 hours.
- Dries to touch and paintable in approximately 2 Hours (24 Hours for oil based paints).
- Store and apply between 4°C to 32°C (40°F and 90°F).

Catalogue Number	Description	Quantity Per Case	Approximate Case Shipping Weight	
MTP300-W	Masters® Trim Plus Painters Caulk Cartridge - White 300 mL	12	14.9 lbs	6.8 kg



©2020 OateySCS. All Rights Reserved. This information is based on data believed to be reliable but Oatey makes no warranties, express or implied, as to its accuracy and assumes no liability arising out of its use. The data listed falls within the normal range of product properties but should not be used to establish specification limits or used alone as the basis of design. Oatey's liability to purchasers is expressly limited to the terms and conditions of sale. Oatey is a trademark of Oatey Co. Oatey Co. is part of the Oatey family of companies. All other trademarks can be found on www.oatey.ca.