

## PAINTABLE SILICONE

MASTERS® PAINTABLE SILICONE creates a water-tight, mildew and crack resistant seal, making it ideal for kitchen, bath and laundry rooms. The tube is easily squeezed by hand to give a consistent bead in tight spaces where a caulking our simply can't reach. The re-sealable cap prevents product from drying out after opening.

MASTERS® PAINTABLE SILICONE is rated for interior and exterior use from -20°F to 180°F (-29°C to 82°C) once cured. It has superior flexibility and adhesion characteristics making it ideal for:

- Tub/shower surrounds
- Kitchen, bath, and laundry room sinks
- Countertops and backsplashes
- Tiling
- Window frames
- Sidina

## **Directions:**

- All surfaces must be clean, free of dirt, oil, old silicone and other debris that could deter adhesion.
- Remove cap and cut nozzle to desired angle and opening size.
- Run a continuous bead along the joint, keeping the squeeze tube ahead of the nozzle.
- Tool to a smooth finish. Excess, uncured sealant can be removed with soap and water.
- Allow MASTERS® PAINTABLE SILICONE to cure fully before exposing to water (approx. 72 hours).
- Dries to touch and latex paintable in approx. 2 hours (24 hours for oil based paint).
- Cleans up with water prior to curing. Clear sealant applies white and dries clear.
- Store and apply between 40°F and 90°F (4°C to 32°C).



Catalogue Number	Description		Approximate Case Shipping Weight	
MPS162-W	MASTERS® Paintable Silicone Squeeze Tube - White- 162 mL	12	5.3 lbs.	2.4 kg
MPS162-C	MASTERS® Paintable Silicone Squeeze Tube - Clear - 162 mL	12	5.3 lbs	2.4 kg



























