



CLOBBER® DRAIN AND WASTE SYSTEM CLEANER TECHNICAL SPECIFICATION

Job Name _____	Item # _____
Location _____	
Engineer _____	Contractor _____
PO # _____	Tag _____
Representative _____	

DESCRIPTION

- A heavy-duty, sulfuric acid drain solvent formulated specifically for emergency use by professionals. Heavier than water, Clobber flows quickly to the blockage allowing special wetting agents to rapidly clear drain, sewer or waste line. It disintegrates paper, rags, sanitary products, grease, sludge, soap, fat, wood, hair, all types of food and organic matter.
- Clobber is formulated with 93% virgin sulfuric acid concentrate and additives that inhibit corrosive action on ferrous and non-ferrous metals. In an independent laboratory test*, Clobber was rated superior to similar type products in preventing corrosion. Because Clobber causes a significant rise in temperature when added to water, it can be used to thaw frozen lines.
- Will not harm septic tanks, cesspools, drainage fields and leaching systems when used according to directions.
- Clobber comes in a molded-handle plastic jug with child-proof caps preventing accidental openings. It is sealed in a plastic bag with warning tags. Jugs are packed in D.O.T. approved cartons. A SAF-T-POR spout is included with each 1/2 gallon jug of Clobber to permit safe, easy pin-point application without hazardous spilling.

*Test available upon request.

SPECIAL NOTICE

This powerful chemical may cause serious injury or damage in the hands of unskilled people. Therefore, it is Hercules strict policy that Clobber may not be sold to any user who is not a Professional: that is, anyone who is not regularly engaged in the maintenance of drain lines as a function of his/her occupation.

APPLICATION / USES

- Use **Clobber** to disintegrate organic matter quickly to unclog drains, sewer and other waste lines or thaw frozen lines.
- **Clobber** may be used on cast iron, steel, copper, brass, lead and plastic pipe.

*For special applications which may not be covered on this or other Oatey literature, please contact Oatey Technical Services Department by phone 1-800-321-9532, or fax 1-800-321-9535, or visit our technical database web-site at www.Oatey.com.

PHYSICAL PROPERTIES / INGREDIENTS

PHYSICAL PROPERTIES	
Boiling Point	334°F
Solubility in water	Completely
Appearance/color/odor	Translucent reddish medium brown liquid. Pungent sulfurous odor.



PRODUCT NUMBER	SIZE	PACKING	WEIGHT/CASE
20205	1 qt.	12	49.0 lbs.
20211	1/2 gal.	6	50.0 lbs.

MATERIAL SAFETY INFORMATION

FOR MORE INFORMATION ON THIS PRODUCT, REQUEST SAFETY DATA SHEET (SDS) #7342E

For Delivery by Fax	Call 1-800-321-9535
Internet	See SDS section of www.Oatey.com
HMIS® ratings	Health: 3 Flammability: 3 Physical hazard: 0

Access BIM/Revit content through www.oatey.com



CLOBBER® DRAIN AND WASTE SYSTEM CLEANER

TECHNICAL SPECIFICATION

PRECAUTIONS

- DO NOT use **Clobber** where other drain chemicals, hot water, or bleach are present.
- **Keep out of reach of children.**
- DO NOT allow **Clobber** in contact with non-acid resistant enamel, stainless steel, chrome, aluminum, galvanized and certain plastics.
- DO NOT use plunger when **Clobber** is in drain.
- DO NOT apply **Clobber** through garbage disposals.
- Avoid backup from drain opening by closing all connecting drains until this product is flushed from system.
- Stand clear of drain openings immediately during and after use.
- DO NOT get in eyes, on skin or on clothing. Causes severe burns to skin, eyes and mucous membranes.
- DO NOT breath vapors or mist. Inhaling vapors or mist may cause permanent lung damage.
- Causes permanent damage or death if swallowed.
- Wear heavy acid resistant gloves and goggles or face shield when handling.
- Keep container closed when not in use. Avoid spills - this product will attack all organic material.
- Use original container only - DO NOT transfer.
- Store in a cool, dry place away from oxidizing materials.
- Provide sufficient ventilation to prevent buildup and inhalation of vapors or mist.
- DO NOT add water or any other chemical to contents because of violent reaction.
- Wash contaminated equipment, shoes, and clothing thoroughly after handling.
- DO NOT use **Clobber** to remove stoppages due to sand, stone, cement or plaster. (Use Hercules Sizzle.)
- **Clobber** is a powerful acid - packaged for safe handling and application. It must always be handled with care. Label directions and precautions must be strictly observed. **Clobber** is packaged in compliance with the Federal Hazardous Substances Act and the Poison Prevention Packaging Act of 1970.
- **Clobber is FOR PROFESSIONAL USE ONLY.** DO NOT leave remaining product unattended or with consumer for any reason. NOT FOR SALE TO OR USE BY CONSUMERS.

DIRECTIONS

WEAR GOGGLES OR FACE SHIELD AND RUBBER GLOVES. HOLD PRODUCT AT ARM'S LENGTH.

1. Remove standing water from drain.
2. Determine **Clobber** dosage and "ALLOW TO STAND" time for type of facility from table below.
3. Put on acid-resistant gloves and goggles or face shield. Stand clear of drain opening.
4. To open container, place on a flat surface. Hold bottle with one hand and unscrew cap taking care not to squeeze or tilt bottle.
5. Slowly pour a small amount of **Clobber** (less than 1/4 pint) DIRECTLY INTO DRAIN OPENING. Keep face and hands away from opening.
6. If no "bubbling" or backup occurs, add rest of dosage slowly and carefully. DO NOT splash or spill **Clobber** outside of drain opening. Immediately recap container tightly after use.
7. After pouring **Clobber** into drain, immediately place inverted dishpan, bucket or other deep container over drain opening to protect against possible eruption of drain contents and acid.
8. Allow to stand for recommended time before flushing.
9. Flush by adding one-quart cold water. Wait 5 minutes. If line is clear, flush thoroughly with cold water.
10. Recommended dosages will open most lines and drains. If stoppage persists, repeat dosage, "ALLOW TO STAND" time and flush procedures.

FACILITY	DOSAGE	ALLOW TO STAND
Small drains, waste lines & traps	1/2 pint	5 to 15 minutes
3" or 4" lines	1 quart	15 to 30 minutes
6" or 8" lines	1/2 gallon	15 to 30 minutes
Urinals	1 pint	15 minutes
Toilet bowls	DO NOT use Clobber.	

Frozen Lines	Repeat as needed
Grease Traps	Use grease dissolving Hercules Wham

Access BIM/Revit content through www.oatey.com