



CRYO-TEK™ RTU-35 READY TO USE

A pre-mixed virgin (not recycled) propylene glycol product with corrosion inhibitors

Formulated for use on all metals

Our triple-protection inhibitor package stabilizes PH to prevent corrosion, chelates, hard water minerals, and inhibits the formation of scale and sediment.

- Keeps system clean and operating efficiently.
- Improves heat transfer and minimizes wear to moving parts.

APPLICATIONS

- Hydronic heating systems
- Aluminum heat exchangers
- Air-hydronic heat pumps and furnaces
- Water based heat extraction systems
- Cooling systems and chillers
- Refrigerating systems
- Cooling towers
- Industrial heat transfer
- Plumbing winterization
- Snow melt systems
- Fire hydrant winterization
- Cooling coil defrosting
- In-floor heating
- Pipe tracing



CERTIFIED PERFORMANCE

Freeze Protection Down To:

0°F / -18°C

Pumpable Down To:

-20°F / -29°C

Burst Protection Down To:

-60°F / -50°C

For application, freeze protection and specific dilutions, view submittal sheet at Oatey.ca.

Product Number	Description	UPC
35350	Cryo-Tek™ RTU-35 - 5 gallon / 20 L	032628353503
35351	Cryo-Tek™ RTU-35 - 55 gallon / 208 L	032628353510

Call your Oatey Sales Representative for more information.



©2022 OateySCS. All Rights Reserved. This information is based on data believed to be reliable but Oatey makes no warranties, express or implied, as to its accuracy and assumes no liability arising out of its use. The data listed falls within the normal range of product properties but should not be used to establish specification limits or used alone as the basis of design. Oatey's liability to purchasers is expressly limited to the terms and conditions of sale. Oatey is a trademark of Oatey Co. Oatey Co. is part of the Oatey family of companies. All other trademarks can be found on www.oatey.ca.