



POWER FLOW™ HEATING OIL ENERGIZER TECHNICAL SPECIFICATION

Job Name _____	Item # _____
Location _____	
Engineer _____	Contractor _____
PO # _____	Tag _____
Representative _____	

DESCRIPTION

- A fuel oil additive which improves combustion efficiency, conserves energy, and reduces fuel oil waste in heating systems.
- Each 16-ounce container treats up to 275-gallons of fuel oil.
- Cleans strainers, nozzles, pumps and burners, minimizing breakdowns from clogged lines, strainers or nozzles and water-blocked filters.
Power Flow in fuel oil is a sludge and water dispersant, which prevents waxing and jelling of oil, and inhibits formation of rust in the tank. Product prevents ice formation and freeze-up of fuel oil line assuring a steady flow of fuel in any kind of weather. Reduces soot formation by increasing burner efficiency.
- **Power Flow** also protects fuel oil during summer storage.

APPLICATION/USES

- Use to improve combustion efficiency, conserve energy, reduce fuel waste and clean strainers, filters, nozzles, pumps, and burners. Emulsifies water from condensation.
- Use **Power Flow** in fuel oil systems.
- *For special applications which may not be covered on this or other Oatey literature, please contact Oatey Technical Services Department by phone 1-800-321-9532, or fax 1-800-321-9535, or visit our technical database web-site at www.Oatey.com.

APPROVALS AND LISTINGS

N.Y.F.D. Permit No. 210330

WARNINGS OR CAUTIONS

- Read all cautions and directions carefully before using this product.
- Keep out of reach of children.
- Harmful or fatal if swallowed. Contains mineral spirits.
- Avoid breathing mist or fumes. Use with adequate ventilation.
- Prolonged exposure to vapors may cause headaches, or dizziness.
- Wash thoroughly after handling.

DIRECTIONS FOR USE

Pour 16-oz. container of **Power Flow** into oil tank before each oil delivery. For tanks larger than 275 gallons use proportionally more **Power Flow**.



PHYSICAL PROPERTIES

Specific Gravity 60°F - 65°F	0.8
Solubility in Water	Negligible
Boiling Point	317-388°F/158-198°C
Appearance and Color	Light brown color. Hydrocarbon odor.

MATERIAL SAFETY INFORMATION

FOR MORE INFORMATION ON THIS PRODUCT, REQUEST SAFETY DATA SHEET (SDS) #7323C

For Delivery By Fax	Call 1-800-321-9535
Internet	See SDS section of www.Oatey.com
HMIS® ratings	Health: 2 Flammability: 2 Physical hazard: 0

PRODUCT NUMBER	SIZE	PACKING	WEIGHT/CASE
35302	1 pt.	24	27.0 lbs
35302R	1 pt.	6	

Access BIM/Revit content through www.oatey.com