Datey OATEY® FAUCET SUPPLY LINES TECHNICAL SPECIFICATION

SPECIFICATIONS

Oatey[®] Faucet Supply Lines are designed to quickly and easily connect the water supply to your faucet. Constructed of durable, high-quality corrosion-resistant material, Oatey connectors bend freely and will not kink. These supply lines come in a variety of sizes and connection types. Oatey products have earned the trust of plumbing professionals for over 100 years.

APPROVALS AND LISTINGS

Listings & Certifications				
NSF/ANSI/CAN 61-2021	IAPMO Certified			
NSF/ANSI/CAN 372-2022	IAPMO Certified			
ASME A112.18.6-2018/ CSA B125.6	IAPMO Certified			
UPC	IAPMO Certified			

FEATURES & MATERIALS

Operating Specifications			
Temperature	40F to 160F		
Pressure	125 PSI Maximum		

Component	Material Composition		
Inner Hose	PVC		
Ferrule	304 Stainless Steel		
Washer	EPDM		
Compression Nut	Brass, Plated		
Compression Ring	Brass, Plated		


Tubing Diameter

0.30" ID (0.49" OD)

Job Name Location		Item #
Engineer	Contractor	
P0 #	Tag	
Representative		



BRAIDED STAINLESS STEEL



Select √	Product Number	Dimension A (Inlet Connection)	Dimension B (Outlet Connection)	Dimension C (Length Inches)	Case Qty
	SL72SC	3/8 COMP	3/8 CU	12	25
	SL75SC	3/8 COMP	3/8 CU	20	25
	SF215C	3/8 COMP	1/2 FIP	6	25
	SF216C	3/8 COMP	1/2 FIP	9	25
	SL02SC	3/8 COMP	1/2 FIP	12	25
	SL03SC	3/8 COMP	1/2 FIP	16	25
	SL05SC	3/8 COMP	1/2 FIP	20	25
	SL07SC	3/8 COMP	1/2 FIP	30	25
	SL08SC	3/8 COMP	1/2 FIP	36	25
	SL182SC	1/2 COMP	1/2 FIP	12	25
	SL183SC	1/2 COMP	1/2 FIP	16	25
	SL185SC	1/2 COMP	1/2 FIP	20	25
	SL187SC	1/2 COMP	1/2 FIP	30	10
	SL142SC	1/2 FIP	1/2 FIP	12	25
	SL145SC	1/2 FIP	1/2 FIP	20	25