

SPECIFICATIONS

Oatey® Water Heater Supply Lines are designed to quickly and easily connect the water supply to your water heater. Constructed of durable, high-quality corrosion-resistant material, Oatey connectors bend freely and will not kink. These supply lines come in a variety of sizes and connection types. Oatey products have earned the trust of plumbing professionals for over 100 years.

APPROVALS AND LISTINGS

| Listings & Certifications | | | | |
|------------------------------------|-----------------|--|--|--|
| NSF/ANSI/CAN 61-2021 | IAPMO Certified | | | |
| NSF/ANSI/CAN 372-2022 | IAPMO Certified | | | |
| ASME A112.18.6-2018/ CSA B125.6 | IAPMO Certified | | | |
| UPC | IAPMO Certified | | | |

FEATURES & MATERIALS

| Operating Specifications | | | | | |
|--------------------------|-----------------|--|--|--|--|
| Temperature | 40F to 160F | | | | |
| Pressure | 125 PSI Maximum | | | | |
| Pressure | 125 PSI Maximum | | | | |


| Component | Material Composition | | |
|------------------------|-----------------------------|--|--|
| Inner Hose | PVC | | |
| Braiding | 304 Stainless Steel | | |
| Ferrule | 304 Stainless Steel | | |
| Washer | EPDM | | |
| Compression Nut | Brass, Plated | | |
| Compression Ring | Brass, Plated | | |

| Tubing Diameter | 0.73" ID (1.01" OD) |
|------------------------|---------------------|
|------------------------|---------------------|

| Job Name | Item # |
|------------------|------------|
| Engineer | Contractor |
| P0 # | Tag |
| Representative _ | |



BRAIDED STAINLESS STEEL



| Select | Product Number | Dimension A (Inlet Connection) | Dimension B (Outlet Connection) | Dimension C (Length Inches) | Case Qty |
|--------|-------------------|--------------------------------------|---------------------------------------|-----------------------------------|-------------|
| | SH94SC | 3/4 FIP | 3/4 FIP | 18 | 10 |
| | SH96SC | 3/4 FIP | 3/4 FIP | 24 | 10 |