



DISC SEAL

SEALING MADE SIMPLE

Cherne® Disc Seals are designed to block flow or provide bypass flow in underground pipes with a low backpressure. Used for pipe construction, rehabilitation, cleaning and testing, these plugs can be separated into two halves to effortlessly fit through any manhole.

GREAT SEALING RANGE

- Field-replaceable double bladders provide leakproof seal
- 5 PSI maximum backpressure

EASY TO USE

- Made of lightweight, corrosion-resistant aluminum
- Includes handles for easy installation and transport
- Separate plug into two halves

TEST
WINNER
BEST™



#104818 shown

PART NUMBER	DISC SEAL SIZE	MAX BACK PRESSURE	BYPASS DIAMETER	WEIGHT
102418	24 IN	5 PSI	2 IN	65.52 LB
102718	27 IN	5 PSI	2 IN	74.72 LB
103018	30 IN	5 PSI	2 IN	85.07 LB
103318	33 IN	5 PSI	2 IN	95.05 LB
103618	36 IN	5 PSI	2 IN	105.38 LB
103918	39 IN	5 PSI	2 IN	126.72 LB
104218	42 IN	5 PSI	2 IN	138.35 LB
104518	45 IN	5 PSI	2 IN	150.32 LB
104818	48 IN	5 PSI	2 IN	162.69 LB
105418	54 IN	5 PSI	2 IN	188.45 LB
106018	60 IN	5 PSI	2 IN	215.58 LB
106618	66 IN	5 PSI	2 IN	244.06 LB
107218	72 IN	5 PSI	2 IN	329.34 LB
107818	78 IN	5 PSI	2 IN	367.29 LB
108418	84 IN	5 PSI	2 IN	405 LB
109018	90 IN	5 PSI	2 IN	444.39 LB
109618	96 IN	5 PSI	2 IN	485.13 LB



#103618 shown



Find us on

©2022 OateySCS. All Rights Reserved. This information is based on data believed to be reliable but Oatey makes no warranties, express or implied, as to its accuracy and assumes no liability arising out of its use. The data listed falls within the normal range of product properties but should not be used to establish specification limits or used alone as the basis of design. Oatey's liability to purchasers is expressly limited to the terms and conditions of sale. Oatey is a trademark of Oatey Co. Oatey Co. is part of the Oatey family of companies. All other trademarks can be found on Oatey.com.