

# INSTRUCTION GUIDE

## QUIET PIPES® HAMMER ARRESTOR

Oatey

The Quiet Pipes® Hammer Arrestor is equipped with a 1/2" Male CPVC Copper Tube Sized (CTS) adapter. You must first install a tee in the water line to accommodate the Quiet Pipes® Hammer Arrestor. The Quiet Pipes® Hammer Arrestor will solvent weld into the 1/2" CPVC tee. The Quiet Pipes® Hammer Arrestor can be installed horizontally or vertically.



- 1** Turn off the water supply to the valve.
- 2** Cut water line and install a tee. Both ends of the tee must be solvent welded to the pipe. Using Oatey CPVC Solvent Cement and Primer is recommended.
- 3** Solvent weld Quiet Pipes® Hammer Arrestor into CPVC tee and allow for recommended cure time.
- 4** Turn the water on and check for leaks.

©2021 Oatey SCS. All Rights Reserved. This information is based on data believed to be reliable but Oatey makes no warranties, express or implied, as to its accuracy and assumes no liability arising out of its use. The data listed falls within the normal range of product properties but should not be used to establish specification limits or used alone as the basis of design. Oatey's liability to purchasers is expressly limited to the terms and conditions of sale. Oatey is trademark of Oatey Co. All other trademarks can be found [www.Oatey.com](http://www.Oatey.com).