



BLUE LAVA™

HOT PVC CEMENT

Oatey® Hot Medium Blue Lava™ PVC Cement is formulated for wet conditions or situations involving fast installation of pressurization of PVC pipe and fittings up to 6" diameter with interference fit.

DESCRIPTION

- Extremely fast setting thick formula clings to pipe in wet and underwater applications
- Preferred formula for emergency, repair, and cut in work
- Medium body blue cement for use on all schedules and classes of PVC pipe and fittings up to 6" diameter with interference fit
- No primer needed where local code permits
- Recommended for potable water, sewer, and DWV applications
- Recommended application temperature 40°F to 110°F / 4°C to 43°C
- Lo-VOC Solvent Cement meets California South Coast Air Quality Management District (SCAQMD) 1168/316A or BAAQMD Method 40 and various environmental requirements
- Meets ASTM D2564



Product Number	Size	Carton Quantity	Description	UPC
32160	4 oz.	24	Oatey® Hot Medium Blue Lava PVC Cement	038753321608
32161	8 oz.	24	Oatey® Hot Medium Blue Lava PVC Cement	038753312613
32162	16 oz.	24	Oatey® Hot Medium Blue Lava PVC Cement	038753312620
32163	32 oz.	12	Oatey® Hot Medium Blue Lava PVC Cement	038753312637
32164	Gallon	6	Oatey® Hot Medium Blue Lava PVC Cement	038753321646

Call your Oatey Sales Representative for more information.



©2019 OateySCS. All Rights Reserved. This information is based on data believed to be reliable but Oatey makes no warranties, express or implied, as to its accuracy and assumes no liability arising out of its use. The data listed falls within the normal range of product properties but should not be used to establish specification limits or used alone as the basis of design. Oatey's liability to purchasers is expressly limited to the terms and conditions of sale. Oatey is a trademark of Oatey Co. Oatey Co. is part of the Oatey family of companies. All other trademarks can be found on www.oatey.com.