SAFETY DATA SHEET



1. Identification

Product identifier Harvey P-12 PVC Heavy Duty Clear or P-12G Gray

Cement Other means of identification

SDS number 1102EV

Synonyms Part Numbers: 018200, 018200V, 018210V, 018220V, 018220V, 018230V, 018230V,

018240, 018240V, 018270, 018270V, 018280, 018280V, 018290, 018290V

Recommended use Joining PVC Pipes
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information Company

Name William H. Harvey Company Address 4334 South 67th Street

Omaha, NE 68117

Telephone 216-267-7100 E-mail info@oatey.com

Transport Emergency Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)

Emergency First Aid 1-877-740-5015
Contact person MSDS Coordinator

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsAcute toxicity, oralCategory 4Skin corrosion/irritationCategory 2

Serious eye damage/eye irritation Category 2A

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters

airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May

cause drowsiness or dizziness.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only outdoors or in a

well-ventilated area. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective

gloves/protective clothing/eye protection/face protection.

Response Rinse mouth. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If

eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash

before reuse. In case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Harvey PVC Heavy Duty Clear or Gray Cement SDS US
920700 Version #: 03 Revision date:7-01-2022 Issue date:8-4-2014 1 / 10

Hazard(s) not otherwise classified (HNOC)

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May form explosive peroxides. Contains a chemical classified by the US EPA as a suspected possible carcinogen.

Supplemental information

Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%	
Furan, Tetrahydro-	109-99-9	30-60	
2-Propanone	67-64-1	10-30	
Cyclohexanone	108-94-1	10-30	
Polyvinyl chloride	9002-86-2	10-30	
Methyl ethyl ketone	78-93-3	5-10	
Colloidal silicon dioxide	112945-52-5	1-5	

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON Inhalation CENTER or doctor/physician if you feel unwell.

Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin Skin contact irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before

reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs,

keep head low so that stomach content doesn't get into the lungs. Aspiration may cause

pulmonary edema and pneumonitis.

Most important symptoms/effects, acute and delayed

Indication of immediate medical attention and special

treatment needed

General information

Ingestion

Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain. Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation.

immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Specific hazards arising from

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

the chemical

Specific methods General fire hazards Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapor. This product contains tetrahydrofuran that may form explosive organic peroxide when exposed to air or light or with age.

SDS US 2/10 920700 Version #: 03 Revision date:7-01-2022 Issue date:8-4-2014

Harvey PVC Heavy Duty Clear or Gray Cement

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors or mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage Precautions for safe handling

Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not taste or swallow. Avoid breathing mist or vapor. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep in an area equipped with sprinklers.

Value

Form

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA
Components

•	71		
Colloidal silicon dioxide (CAS 112945-52-5)	TWA	0.8 mg/m3	Unspecified.
		20 mppcf	Unspecified.
US. OSHA Specifically Regulated S	Substances (29 CFR 1910.1001		1
Components	Туре	Value	
Polyvinyl chloride (CAS 9002-86-2)	STEL	5 ppm	
	TWA	1 ppm	
US. OSHA Table Z-1 Limits for Air	Contaminants (29 CFR 1910.1	000)	
Components	Туре	Value	Form
2-Propanone (CAS 67-64-1)	PEL	2400 mg/m3	
,		1000 ppm	
Cyclohexanone (CAS 108-94-1)	PEL	200 mg/m3	
•		50 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	PEL	590 mg/m3	
		200 ppm	

Type

Harvey PVC Heavy Duty Clear or Gray Cement

SDS US

920700 Version #: 03 Revision date:7-01-2022 Issue date:8-4-2014

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Methyl ethyl ketone (CAS	PEL	590 mg/m3	
78-93-3)		200 ppm	
Polyvinyl chloride (CAS 9002-86-2)	PEL	5 mg/m3	Respirable fraction.
9002-86-2)		15 mg/m3	Total dust.
JS. OSHA Table Z-3 (29 CFR 1910.	.1000)	Ŭ	
Components	Туре	Value	
Colloidal silicon dioxide CAS 112945-52-5)	TWA	0.8 mg/m3	
		20 mppcf	
JS. ACGIH Threshold Limit Values	\$		
Components	Туре	Value	Form
2-Propanone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Cyclohexanone (CAS 108-94-1)	STEL	50 ppm	
,	TWA	20 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	STEL	100 ppm	
	TWA	50 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL	300 ppm	
	TWA	200 ppm	
Polyvinyl chloride (CAS 9002-86-2)	TWA	1 mg/m3	Respirable fraction.
J.S NIOSH			
Components	Туре	Value	Form
Colloidal silicon dioxide	REL	6 mg/m3	Unspecified.
(CAS 112945-52-5) US. NIOSH: Pocket Guide to Chem	nical Hazards		
Components	Туре	Value	
2-Propanone (CAS 67-64-1)	TWA	590 mg/m3	
	IVVA	390 110/113	
e riopanone (one or of i)	TVVA		
Colloidal silicon dioxide	TWA	250 ppm 6 mg/m3	
Colloidal silicon dioxide (CAS 112945-52-5)	TWA	250 ppm 6 mg/m3	
Colloidal silicon dioxide (CAS 112945-52-5) Cyclohexanone (CAS		250 ppm 6 mg/m3 100 mg/m3	
Colloidal silicon dioxide (CAS 112945-52-5) Cyclohexanone (CAS 108-94-1)	TWA TWA	250 ppm 6 mg/m3 100 mg/m3 25 ppm	
Colloidal silicon dioxide (CAS 112945-52-5) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS	TWA	250 ppm 6 mg/m3 100 mg/m3	
Colloidal silicon dioxide (CAS 112945-52-5) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS	TWA TWA STEL	250 ppm 6 mg/m3 100 mg/m3 25 ppm 735 mg/m3 250 ppm	
Colloidal silicon dioxide (CAS 112945-52-5) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9)	TWA TWA	250 ppm 6 mg/m3 100 mg/m3 25 ppm 735 mg/m3 250 ppm 590 mg/m3	
Colloidal silicon dioxide (CAS 112945-52-5) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9)	TWA TWA STEL TWA	250 ppm 6 mg/m3 100 mg/m3 25 ppm 735 mg/m3 250 ppm 590 mg/m3 200 ppm	
Colloidal silicon dioxide (CAS 112945-52-5) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS	TWA TWA STEL	250 ppm 6 mg/m3 100 mg/m3 25 ppm 735 mg/m3 250 ppm 590 mg/m3	
Colloidal silicon dioxide (CAS 112945-52-5) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS	TWA TWA STEL TWA STEL	250 ppm 6 mg/m3 100 mg/m3 25 ppm 735 mg/m3 250 ppm 590 mg/m3 200 ppm 885 mg/m3 300 ppm	
Colloidal silicon dioxide (CAS 112945-52-5) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS	TWA TWA STEL TWA	250 ppm 6 mg/m3 100 mg/m3 25 ppm 735 mg/m3 250 ppm 590 mg/m3 200 ppm 885 mg/m3	

Harvey PVC Heavy Duty Clear or Gray Cement

920700 Version #: 03 Revision date: 7-01-2022 Issue date: 8-4-2014 4 / 10

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time	
2-Propanone (CAS 67-64-	1) 50 mg/l	Acetone	Urine	*	
Cyclohexanone (CAS 108-94-1)	80 mg/l	1,2-Cyclohexan ediol, with hydrolysis	Urine	*	
	8 mg/l	Cyclohexanol, with hydrolysis	Urine	*	
Furan, Tetrahydro- (CAS 109-99-9)	2 mg/l	Tetrahydrofura n	Urine	*	
Methyl ethyl ketone (CAS 78-93-3)	2 mg/l	MEK	Urine	*	

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Cyclohexanone (CAS 108-94-1) Skin designation applies.

US - Tennessee OELs: Skin designation

Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin. Furan, Tetrahydro- (CAS 109-99-9) Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing. Other

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

When using, do not eat, drink or smoke. Wash hands after handling and before eating.

9. Physical and chemical properties

Appearance Opaque.or Translucent.

Liquid. Physical state **Form** Liquid. Color Gray or Clear.

Odor Solvent. Not available. **Odor threshold** Not available. pН Melting point/freezing point Not available.

Initial boiling point and boiling range

151 °F (66.11 °C)

14.0 - 23.0 °F (-10.0 - -5.0 °C) Flash point

Evaporation rate

Harvey PVC Heavy Duty Clear or Gray Cement 920700 Version #: 03 Revision date: 7-01-2022 Issue date: 8-4-2014 5/10

SDS US

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits Not available.

(%)

Flammability limit - upper

Flammability limit - lower

(%)

Not available.

Not available. **Explosive limit - lower (%)** Not available. **Explosive limit - upper (%)**

Vapor pressure 145 mm Hg @ 20 C

Vapor density 2.5

Relative density 0.88 - 0.92

Solubility(ies)

Negligible Solubility (water) Not available. Partition coefficient

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Viscosity 1200 - 2500 cP

Other information

Bulk density 7.5 lb/gal

See Can Label VOC (Weight %)

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Ammonia. Amines. Isocyanates. Caustics.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May be fatal if swallowed and enters airways. Vapors have a narcotic effect and may cause

headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful. May cause

irritation to the respiratory system.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

May be fatal if swallowed and enters airways. Harmful if swallowed. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness,

nausea and vomiting.

Information on toxicological effects

May be fatal if swallowed and enters airways. Narcotic effects. May cause respiratory irritation. **Acute toxicity**

Components **Species Test Results**

Cyclohexanone (CAS 108-94-1)

Acute Dermal

LD50 Rabbit 948 mg/kg

Inhalation

LC50 Rat 8000 ppm, 4 hours

Harvey PVC Heavy Duty Clear or Gray Cement SDS US 920700 Revision date: 7-01-2022 6/10 Version #: 03 Issue date: 8-4-2014

Components Species Test Results

Oral

LD50 Rat 1540 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer. In 2012 USEPA Integrated Risk Information System (IRIS)

reviewed a two species inhalation lifetime study on THF conducted by NTP (1998). Male rats developed renal tumors and female mice developed liver tumors while neither the female rats nor the male mice showed similar results. Because the carcinogenic mechanisms could not be identified clearly in either species for either tumor, the EPA determined that the male rat and female mouse findings are relevant to the assessment of carcinogenic potential in humans. Therefore, the IRIS review concludes that these data in aggregate indicate that there is "suggestive evidence of carcinogenic potential" following exposure to THF by all routes of exposure. This product contains polyvinyl chloride (PVC) that is not a fabricated product, and is therefore, defined and regulated as a toxic and hazardous substance under 29 C.F.R. § 1910.1017 due to the presumed presence of residual vinyl chloride monomer. The concentrations

1910.1017 due to the presumed presence of residual vinyl chloride monomer. The concentrations of residual vinyl chloride calculated to be contained in this product are well below the threshold for

classification in accordance with 29 C.F.R. § 1910.1200.

IARC Monographs. Overall Evaluation of Carcinogenicity

Colloidal silicon dioxide (CAS 112945-52-5)

Cyclohexanone (CAS 108-94-1)

Polyvinyl chloride (CAS 9002-86-2)

3 Not classifiable as to carcinogenicity to humans.

3 Not classifiable as to carcinogenicity to humans.

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Polyvinyl chloride (CAS 9002-86-2) Cancer

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Respiratory tract irritation. Narcotic effects.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

Cyclohexanone (CAS 108-94-1)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 481 - 578 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

 2-Propanone (CAS 67-64-1)
 -0.24

 Cyclohexanone (CAS 108-94-1)
 0.81

 Furan, Tetrahydro- (CAS 109-99-9)
 0.46

 Methyl ethyl ketone (CAS 78-93-3)
 0.29

Mobility in soil No data available.

^{*} Estimates for product may be based on additional component data not shown.

^{*} Estimates for product may be based on additional component data not shown.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material **Disposal instructions**

> and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN1133 UN number Adhesives **UN proper shipping name**

Transport hazard class(es)

3 Class Subsidiary risk 3 Label(s) Ш **Packing group**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

T11, TP1, TP8, TP27 **Special provisions**

150 **Packaging exceptions** Packaging non bulk 201 Packaging bulk 243

IATA

UN1133 **UN number** UN proper shipping name Adhesives

Transport hazard class(es)

Class 3 Subsidiary risk Ш Packing group **Environmental hazards** No. **ERG Code** 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1133 **UN** proper shipping name **ADHESIVES**

Transport hazard class(es)

3 Subsidiary risk Packing group Ш **Environmental hazards**

Marine pollutant No. **EmS** F-E, S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

Harvey PVC Heavy Duty Clear or Gray Cement 8/10 920700 Version #: 03 Revision date: 7-01-2022 Issue date: 8-4-2014

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Polyvinyl chloride (CAS 9002-86-2)

Central nervous system

Liver Rlood Flammability

CERCLA Hazardous Substance List (40 CFR 302.4)

2-Propanone (CAS 67-64-1) LISTED Cyclohexanone (CAS 108-94-1) LISTED Furan, Tetrahydro- (CAS 109-99-9) LISTED Methyl ethyl ketone (CAS 78-93-3) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories**

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

No

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number**

2-Propanone (CAS 67-64-1) 6532 Methyl ethyl ketone (CAS 78-93-3) 6714

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

2-Propanone (CAS 67-64-1) 35 %WV Methyl ethyl ketone (CAS 78-93-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

2-Propanone (CAS 67-64-1) 6532 Methyl ethyl ketone (CAS 78-93-3) 6714

US state regulations

US. Massachusetts RTK - Substance List

2-Propanone (CAS 67-64-1)

Colloidal silicon dioxide (CAS 112945-52-5)

Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3)

US. New Jersey Worker and Community Right-to-Know Act

2-Propanone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3)

Harvey PVC Heavy Duty Clear or Gray Cement 9/10

920700 Version #: 03 Revision date: 7-01-2022 Issue date: 8-4-2014

Polyvinyl chloride (CAS 9002-86-2)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Propanone (CAS 67-64-1)

Colloidal silicon dioxide (CAS 112945-52-5)

Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3)

US. Rhode Island RTK

2-Propanone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3)

US. California Proposition 65

MARNING: This product can expose you to chemicals including Tetrahydrofuran, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

See Section 11 for additional information.

International Inventories

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

On inventory (yes/no)*

Yes

Inventory name

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 04-August-2014 07-01-2022 **Revision date**

Version # 03 Health: 2 **HMIS®** ratings

United States & Puerto Rico

Flammability: 3 Physical hazard: 0

Disclaimer The information in the sheet was written based on the best knowledge and experience currently

available.

SDS US 920700 Version #: 03 Revision date: 7-01-2022 10 / 10 Issue date: 8-4-2014

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).